Crack-Vac 2™

Clean and prepare cracks — dust-free*!



The environmentally effective way to remove dirt and debris from pavement cracks, virtually dust-free.

The **Crafco Crack-Vac 2** is the ultimate tool for pavement crack cleaning and crack sealing preparation. Its high-efficiency air blowers effectively dislodge trapped material, while its powerful vacuum suctions it swiftly away.

It's the only standalone system with this dual function, and the best way to clean pavement cracks and maximize crack sealant longevity!

- The Crack-Vac 2 innovative EZ-glide wand swivels for near 360° mobility, allowing operators to move freely with less fatigue.
- The powerful blower and vacuum create a single-pass solution that clears and prepares cracks with maximum efficiency.
- The EZ Glide Vacuum wand's triple air nozzles inject high pressure air into cracks to force debris out. Simultaneously, the suction port vacuums up debris through the hose into the cyclonic filter system, keeping particulates and fines out of the air.
- The Crafco Crack-Vac 2's HEPA-rated after-filter reduces fugitive dust and crystalline silica particulates to as little as .3 microns,* achieving the industry's lowest occupational exposure limits (OELs).

With the Crack-Vac 2, you can keep your workers and communities safe — and your operation in compliance with pressing environmental legislation.

Crack sealing is the most effective and lowest cost pavement preservation treatment.

 Pavement cracks that are clean, routed or non-routed, prior to crack sealing, provide the longest service life and best return on investment.

The most expensive part of crack sealing is sealing the same crack again!

- Labor makes up 80% of the cost of crack sealing. The combination of routing and cleaning with crack sealing extends pavement life and is the most cost-effective preservation treatment for flexible pavements.
- Using the Crack-Vac 2 delivers superior crack cleaning performance. There is nothing else like it, and no better way to prepare asphalt pavement cracks.
- The Crack-Vac 2 is the only unit on the market designed specifically to clean cracks using a powerful combination of compressed air and suction.

*Per High Efficiency Particulate Air (HEPA) filter standard measures.



Key features standard on all Crack-Vac 2™ models



EZ-Glide Wand & 4-Caster Head



Cyclone Seperator



HEPA Filter (exceeds OSHA standards)



100 Gal Debris Holding Tank w/ Hydraulic Dump









SPECIFICATIONS

		-	
Model/Part No.	Crack-Vac 2: Skid-mounted, ready for truck/trailer mount 60800N	Crack-Vac 2: Skid-mounted w/ compressor, ready for truck/trailer mount 60900N	Trailer for Crack-Vac 2 60350
Dimensions	W 72 in (182 cm) x H 80 in (203 cm) x L 116 in (294 cm)	W 72 in (182 cm) x H 80 in (203 cm) x L 116 in (294 cm)	W 91 in (231 cm) x H 35 in (89 cm) x L 179 in (455 cm)
Shipping Weight	2060 lbs (934 kg)	2360 lbs (1070 kg)	1640 lbs (744 kg)
Compressor	n/a	32 CFM at 100 PSI (Max 150 PSI)	n/a
Blower & Silencer (Air Flow)	437 CFM @3,600 RPM and 16" HG	437 CFM @3,600 RPM and 16" HG	n/a
Air Filtration System	3 Stage, HEPA rated	3 Stage, HEPA rated	n/a
Collection Pail Capacity	4 gal. (15.1 l)	4 gal. (15.1 l)	n/a
Suction Hose (Diameter)	3 in. (7.62 cm)	3 in. (7.62 cm)	n/a
Boom (Adjustable Extension Tube)	72 in. (183 cm)	72 in. (183 cm)	n/a
Vacuum Head (L x W)	7.48 in. (19 cm) x 9.85 in. (25 cm)	7.48 in. (19 cm) x 9.85 in. (25 cm)	n/a
Fuel System (Gas Tank Size)	20 gal. (75.7 l)	20 gal. (75.7 l)	n/a
Battery	12V (Min. 580 cold cranking amps)	12V (Min. 580 cold cranking amps)	n/a

STANDARD FEATURES

- Kohler Command Pro gasoline engine 27 HP (20.1 kW) at 3,600 RPM
- 100 Gallon (378.541 I) holding tank with hydraulic dump
- Cyclone separator
- **HEPA Filter**
- 95" long cab over boom with an additional 72" extension
- EZ-Glide wand
- Light weight suction hose
- Ready for truck or trailer mount

OPTIONS

- Air compressor (kohler gasoline engine CH620
- Extra main cartridge filter
- Extra HEPA filter
- Extra 5 gal pail liner (25 count)
- Dual axle trailer with storage deck
- Various safety and work light kits

PRESERVATION PRODUCTS PAVEMENT

TRAILER OPTIONS

- 2 5/16" Ball Hitch
- Pintle hitch (2 ½" or 3")
- Hitch extension, 18", 28" and 39"
- Truck connector, 7 pin round RV connector, blade terminals
- Truck connector, 7 pin round connector, round
- Truck connector, 6 pin round connector
- Truck connector, 5 pin flat connector
- Cab brake controller
- Breakaway battery w/ charger
- Safety hook w/ latch (2 required)



Two-year warranty on all equipment. One-year warranty on parts purchased through Crafco. Visit www.crafco.com for full warranty coverage.



©2021 Crafco, Inc. April #A1420